

Product sheet

Basic Information

Order Number
Type
Common Number

1548111000
ZN1110
ZN1110



8592920090640

Measuring Unit
Packaging
Net Weight [kg]
Dimensions [mm]
Technical Support


KS
1 / - / - / 10
0,605
70 × 360 × 115
Martin Kubalák, 581261113,
kubalak@emos.cz



Technical Description

type of emergency operation
test
light color
body color
frequency of power voltage
IP rating
material of the diffuser
body material
power voltage
packaging
input current
input power
dimensions
working temperature range
luminous flux
color temperature
output power in emergency
mode
output voltage in emergency
mode

manual button
cool white
white
50/60 Hz
IP65
plastic (PC)
plastic (ABS)
220–240 V AC
1 pc, box
18 mA
3 W
351 × 111 × 63 mm
0 °C to +40 °C
150 lm
6 500 K
3 W
10–50 V DC, constant current



Product sheet

protection class	II
mounting type	attached
warranty period	4 years
source of light	LED
power factor	>0,5
mechanical impact protection	IK08
output voltage	10–72 V DC
backup time	3 h
battery charging time	≥ 24 hours
battery type	LiFePo4
battery capacity	1 500 mAh
battery warranty	2 years
type of emergency light operation	maintained/non-maintained
category	PROFI
line	NESSI