

NIGHT BREAKER SILVER H7

Excellent performance-lifetime ratio



Up to 100% more brightness

More light allows to see farther and therefore react sooner compared to the minimum legal standard




Up to 130 m long beam

For better visibility



Excellent performance-lifetime ratio

For more light at a reasonable lifetime



The OSRAM performance halogen light with best lifetime

With NIGHT BREAKER SILVER, OSRAM offers a performance halogen automotive lamp with an optimized lifetime. OSRAM NIGHT BREAKER SILVER generates up to 100% more brightness compared to the minimum legal standard and a beam which is up to 130 meters long. This allows you to see road signs, obstacles and hazards sooner and the driver is left with more time to react. In addition to this, these automotive lamps have a convincing price-performance ratio and a modern design with an attractive silver cap (H4/H7/H11). The perfect choice for drivers who place high demands on performance and lifetime.

Technical data

Product information

Application (Category and Product specific)	Halogen headlight lamp
---	------------------------

General Product Information

Global order reference	64210NBS
------------------------	----------

Electrical Data


Power input	58 W ¹⁾
Nominal voltage	12.0 V
Nominal wattage	55 W
Test voltage	13.2 V

¹⁾ Maximum

Photometric Data

Nominal luminous flux	1500 lm
Luminous flux tolerance	±10 %

Physical Attributes & Dimensions



Diameter	11.3 mm
Diameter	11.3 mm
Product weight	12.50 g
Length	59.0 mm
Lamp base	PX26d

Lifetime Data

Lifespan B3	330 hr
Lifespan Tc	550 hr

Capabilities

Technology	HAL
------------	-----

Certificates & standards

ECE category	H7
--------------	----

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (RECh)	
Primary article identifier	4052899992771 4052899579187 4052899992719 4052899992511 4052899992634 4062172395113 4062172387576
Candidate list substance 1	No declarable substances contained
Declaration no. in SCIP database	No declarable substances contained

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899579187	NIGHT BREAKER SILVER H7	Unpacked 1	59 mm x 11 mm x 11 mm	0.44 dm ³	13.00 g
4052899579194	NIGHT BREAKER SILVER H7	Shipping carton box 180	345 mm x 255 mm x 240 mm	21.11 dm ³	2852.00 g
4052899992511	NIGHT BREAKER SILVER H7	Blister 1	135 mm x 95 mm x 35 mm	0.44 dm ³	24.00 g
4052899992528	NIGHT BREAKER SILVER H7	Shipping carton box 10	279 mm x 115 mm x 145 mm	4.65 dm ³	330.00 g
4052899992634	NIGHT BREAKER SILVER H7	Folding carton box 1	34 mm x 34 mm x 58 mm	0.44 dm ³	16.00 g
4052899992658	NIGHT BREAKER SILVER H7	Shipping carton box 100	356 mm x 186 mm x 129 mm	8.54 dm ³	1762.00 g
4052899992719	NIGHT BREAKER SILVER H7	Hard Cover Box 2	113 mm x 48 mm x 106 mm	0.44 dm ³	117.00 g
4062172058827	NIGHT BREAKER SILVER H7	Shipping carton box 10	268 mm x 126 mm x 125 mm	4.22 dm ³	670.00 g
4062172387576	NIGHT BREAKER SILVER H7	HFB ECO 2	100 mm x 51 mm x 120 mm	0.44 dm ³	55.00 g
4062172387583	NIGHT BREAKER SILVER H7	Shipping carton box 10	266 mm x 111 mm x 134 mm	3.96 dm ³	354.00 g
4062172395113	NIGHT BREAKER SILVER H7	BLI ECO 1	95 mm x 34 mm x 135 mm	0.44 dm ³	23.00 g
4062172395120	NIGHT BREAKER SILVER H7	Shipping carton box 10	194 mm x 144 mm x 110 mm	3.07 dm ³	285.00 g

Product datasheet

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File	
	User instruction GPRS_Safety symbols instructions
	ref_pim_amsproduct360degreeimages NIGHT BREAKER SILVER H7 64210NBS

Legal advice

Light output compared to the minimum ECE 112 requirements.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

