S1100-R



Product Name: S1100-R Product Number: 700S1100-R

Description Rechargeable torch with 1100 and 120 lumens and sliding focus

Specifications

Housing Aluminium

Lens Ф32mm planoconvex lens

On/off switch Tailcap Switch Battery type 18650 (3500mAH) **CREE XPL LED** Light source Colour temperature (Kelvin) 7500

Focus Sliding style optical focus system

Charger operating voltage 5V/0.9A

Charger output Required: DC5V - 1A max (USB connector)

Output 30 seconds (lumen) 120 (low) / 1100 (high) Run time (hours) down to 1 lumen 22 (low) / 11 (high) Run time (hours) down to 10% of full lumens 18 (low) / 5.5 (high)

Charging time (hours) 5-6 Charging level indicator red, green

110 (low) / 300 (high) Beam distance (m) Beam width (cm) from 1m distance 110 (flood) / 14 (spot)

Protection class IPX5 / IK07 / III (torch) - II (charger) between -20°C and 50°C

Operating temperature range (Celsius)

Type-C USB Charging port

Charging port cover Turn-to-cover type-C USB charging port

Cable for charger 1 m (supplied in box). USB into charger, USB C into torch

General Information

Torch weight (g) 204 incl battery Torch dimensions (cm) Ø3.7 x 14.75 5703296700115 EAN code box (1 pc) EAN code inner carton/display 5703296700122 EAN code outer carton 5703296700139 Harmonized standard code 8513100000

Packaging

Description "PRO" design printed box

18.6x21.1x8.7 Box size (cm)

Box weight (g) 625

4 (inner carton) / 16 (outer carton) Carton quantity (pcs)

Carton size (cm) 25.5 x 19.5 x 19.3 (inner carton) / 40.4 x 41.5 x 26.5 (outer carton)

Carton weight (kg) 2.8 (inner carton) / 11.3 (outer carton)

Features

Lightweight torch with sliding focus

Rechargeable. Hold head and turn tube for access to charging port. Charging indicator (1 x LED), red = charging / green = fully charged

Switch mode: high-off-low-off Turn-to-cover Micro USB charging hole Supplied with pouch and lanyard Supplied with USB C cable for charger



