

# LEDDriving HLT BRIGHT H1

LEDDriving high and low beam lamps for truck




## Cool White color temperature of 6,000 K

Better visibility thanks to daylight effect



## Superior brightness

More light allows to see farther and therefore react sooner. Signs, obstacles and hazards can be recognized sooner



## LED replacement for conventional H1 high and low beam lamps

Reduced glaring thanks to an optimized light distribution



## H1 LED replacement for 24V

LEDDriving HLT BRIGHT replacement lamps offer a modern and intense light with a color temperature of up to 6,000 Kelvin. These replacement lamps are suitable for conventional H1 high and low beam lamps. LEDDriving HLT BRIGHT for high and low beam off-road applications are 24 V compatible and stand out with superior brightness, high compatibility, easier installation due to integrated driver and no radio disturbance. The pair of lamps comes with a 4-year OSRAM guarantee. For precise guarantee conditions please refer to [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee). These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Technical data

Product information

Product type (off-road vs. on-road)	Off-road ≙ H1
Application (Category and Product specific)	Mainly used for Low Beam, High Beam and Fog light applications

General Product Information

Global order reference	64155DWBRT
------------------------	------------


Electrical Data

Power input	13 W
Nominal voltage	24.0 V
Nominal wattage	13 W
Power input tolerance	±20 %
Test voltage	28.0 V

Photometric Data

Nominal luminous flux	1500 lm
Luminous flux tolerance	±20 %
Color temperature	6000 K
Light color LED	Cool white

Physical Attributes & Dimensions



Lamp base	P14.5s
Length	76.2 mm
Diameter	11.8 mm
Product weight	50.00 g

Product datasheet

Lifetime Data

Lifespan Tc	2000 hr
Guarantee	4 years

Capabilities

Technology	LED
------------	-----

Environmental & Regulatory Information



Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of declaration	14-10-2024
Primary article identifier	4062172379755
Declaration no. in SCIP database	In Vorbereitung

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172379755	LEDiving HLT BRIGHT ≙ H1	Folding carton box 2	136 mm x 56 mm x 162 mm	1.23 dm³	201.00 g
4062172379762	LEDiving HLT BRIGHT ≙ H1	Shipping carton box 8	240 mm x 148 mm x 182 mm	6.46 dm³	930.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File	
	User instruction LEDiving HLT BRIGHT
	Brochures LEDiving Retrofits - Exchange overview (EN)

Safety advice

Application advice:For more detailed application information and graphics please see product datasheet and user manual.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

