

SubstiTUBE® T5 HE 28 HF (High Efficiency)

1.2m Ballast compatibility (1149mm)

	compatible
	* compatible but may differ >10% of luminous flux of specification
	not compatible

Brand	Model	Lamps on ballast	ST5 HE28 16W
			Product EAN10 No. 4058075819931 4058075819214 4058075819238
OSRAM	QTi 1x28/54/35/49 GII	1	
	QTi 2x28/54/35/49 GII	2	
	QTP5 1x14-35	1	
	QTP5 2x14-35	2	
	QT-FIT5 1x14-35	1	
	QT-FIT5 2x14-35	2	
	QTz5 1x28/220-240	1	
	QTz5 2x28/220-240	2	
	QTi DALI 1x28/54 DIM	1	* dim not guaranteed
	QTi DALI 2x28/54 DIM	2	* dim not guaranteed
Philips	HF-P 1 14-35 TL5 HE III IDC	1	
	HF-P 2 14-35 TL5 HE III IDC	2	
	HF-Pi 1 28/35/49/54 TL5 EII 220-240	1	
	HF-Pi 2 28/35/49/54 TL5 EII 220-240	2	
	HF-Pi 1 28/35/49/80 TL5 EII 220-240	1	
	HF-Pi 2 28/35/49/80 TL5 EII 220-240	2	
Tridonic	PC 1x14-35 T5 PRO Ip	1	
	PC 2x14-35 T5 PRO Ip	2	
	PC 1x14-35 T5 TOP Ip	1	
	PC 2x14-35 T5 TOP Ip	2	
	PC 1/14-35/49/54 T5 PRO-M Ip	1	
	PC 2/14-35/49/54 T5 PRO-M Ip	2	
	PC 1/14-35/49/80 T5 PRO-M Ip	1	
	PC 1x28 T5 TEC Ip	1	
	PC 2x28 T5 TEC Ip	2	
b,a,g,	BCS35.1FX-11/220-240	1	
	BCS35.2FX-11/220-240	2	

Important

Dimming an LED tube:

Ballast with Dim are conditionally released by LEDVANCE

LED tube dimming curve is different from the curve of a traditional fluorescent.

The performance of dimming is not guaranteed in a dimming application