

Product information sheet


LED Ecobasic Compact T44 E27 11W (75W) 1050lm 830

Bailey nr.: 80100040594

EAN-code: 8714681405949

Type of light source

Lighting technology used	LED
Cap type	E27
Non-directional or directional	NDLS
Mains or non-mains	MLS
Connected light source (CLS)	No
Colour-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Dimmable	No



Specifications

Energy consumption in on-mode (KWh/1000h)	11
Energy Efficiency Class	F
Useful luminous flux (use) in lm	1050
Beam angle correspondence	Sphere (360°)
Correlated colour temperature (K)	3000
On-mode power (Pon) in W	11
Standby power (Psb) in W	0
Networked standby power for CLS (Pnet) in W	-
Colour rendering index	80
Outer dimension (Height) in mm	139
Outer dimensions (Width) in mm	44
Outer dimensions (Depth) in mm	-
Claim of equivalent power	Yes
Equivalent power (W)	75
Chromaticity coordinate (x)	0,44
Chromaticity coordinate (y)	0,403
Peak luminous intensity (cd)	110
Beam angle (°)	220
R9 Colour rendering index	0
Survival factor	0,9
Lumen maintenance factor	0,96
Displacement factor	0,7
Colour consistency in McAdam ellipses	6
Claim CFL-ni	No
Replacement claim (W)	-
Flicker metric	1
Stroboscopic effect metric	0,4
Lifetime L70B50 (h)	15000
Nominal voltage (V)	220-240
Voltage type	AC
Frequency	50/60

Specific precautions

N/A

Spectral power distribution

