



MASTERColour CDM-TC Elite



MASTERC CDM-TC Elite 70W/930 G8.5 1CT/12

Compact, single-ended, very high-efficiency, long-life ceramic metal-halide discharge lamp producing crisp white sparkling light with high color rendering

Warnings and Safety

- · Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- $\boldsymbol{\cdot}$ The luminaire must be able to contain hot lamp parts if the lamp ruptures
- \cdot Use only with electronic control gear
- · Control gear must include end-of-life protection (IEC61167, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Cap-Base	G8.5
Operating Position	UNIVERSAL [Any or Universal (U)]
Flux measurement reference	Sphere
Life to 50% Failures (Nom)	20,000 hour(s)
Light Technical	
Color Code	930 [CCT of 3000K]
Luminous Flux	7,800 lm
Color Designation	Warm White (WW)
Chromaticity Coordinate X (Nom)	0.434
Chromaticity Coordinate Y (Nom)	0.398
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	107 lm/W

Color rendering index (CRI)	90
Arc Length O (Nom)	7.15 mm
Operating and Electrical	
Power Consumption	73.2 W
Voltage (Nom)	85 V
Voltage (Nom)	85 V
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Clear

Datasheet, 2024, January 9 data subject to change

MASTERColour CDM-TC Elite


Bulb Shape	T14
Approval and Application	
Energy Efficiency Class	F
Mercury (Hg) Content (Max)	6.6 mg
Mercury (Hg) Content (Nom)	6.6 mg
Energy Consumption kWh/1000 h	74 kWh
EPREL Registration Number	473265
Product Data	

MASTERC CDM-TC Elite 70W/930 G8.5 1CT/12

Full product name	MASTERC CDM-TC Elite 70W/930 G8.5 1CT/12
Full product code	872790091153400
Order code	928189505131
Material Nr. (12NC)	928189505131
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8727900911534
Numerator - Packs per outer box	12
EAN/UPC - Case	8727900911541

Dimensional drawing

Order product name





 Product
 D (max)
 D (mix)
 L (mix)
 L (max)
 L (max)
 C (max)


 MASTERC CDM-TC Elite 70W/930
 15 mm
 7.15 mm
 51 mm
 53 mm
 52 mm
 85 mm

 G8.5 1CT/12
 5 mm
 1 mm

Photometric data









Light Distribution Diagram - MASTERC CDM-TC Elite 70W/930 G8.5 1CT/12

Spectral Power Distribution Colour - MASTERC CDM-TC Elite 70W/930 G8.5 1CT/12

MASTERColour CDM-TC Elite

Lifetime





Lumen Maintenance Diagram - MASTERC CDM-TC Elite 70W/930 G8.5 1CT/12

Life Expectancy Diagram - MASTERC CDM-TC Elite 70W/930 G8.5 1CT/12



© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.