



Metal industrial luminaire with IP65 - eco

MODUS MEGA LED 1220mm, wide beam, 4x LED , 840, PMMA cover, pendant, 2x600 mA DALI, with gear box

Code: MEGALW4M4V4/1200DALI

EAN: 8596099054793



Luminaire properties

| | | | |
|---------------------------------|--------------------|-------------------------------|---------|
| Product category: | High bay luminaire | Effective luminous flux (lm): | 27000 |
| System power (W): | 173 | Luminaire efficacy (lm/W): | 156 |
| Degree of protection (IP): | IP65 | Mounting method: | Pendant |
| Color housing: | White | Material housing: | Steel |
| Light source included: | Yes | | |
| Fire resistance D: | Yes | | |
| Rated ambient temperature (°C): | -25...+45 | Made in Czech republic: | Yes |

Light source

| | | | |
|----------------------------|-------|------------------------|--|
| Light source type: | LED | Color temperature (K): | 4000 |
| Color rendering index CRI: | 80-89 | Replaceability: | Removeable light source, replaceable ballast |

Optical system

| | | | |
|-----------------|-----------|---------------------|------------|
| Optical system: | C | Reflector: | High-gloss |
| Light sharing: | Symmetric | Material reflector: | Aluminium |

Dimensions

| | | | |
|--------------------|------|--------------|-----|
| Length (mm): | 1224 | Width (mm): | 357 |
| Height/depth (mm): | 90 | Weight (kg): | 11 |

Electrical values

| | | | |
|----------------------|-----------|------------------------|--|
| Voltage type: | AC | Type of control gear: | LED operating device current-controlled |
| Nominal voltage (V): | 220...240 | Control gear included: | Yes |
| Dimming DALI: | Yes | | |