



Atex 2AA

67 waterproof rating and survives drop after drop from up to 1 meter. With the purpose of keeping the user safe, a lanyard loop make for easy access on the job, whilst the orange safety color provides instant recognition. LED technology delivers consistent illumination of up to 150 lumens for a long duration of 10 hours to keep you active for longer.

Specifications

- Beam
- 150 Lumens
- 12 Hours
- 175
- IPX7
- 1 M
- Lumens (brightness)
- Run time
- Beam distance
- Weatherproof (water proof)
- Impact resistance

Features

- Intrinsically safe (ATEX) handheld
- -20°C to 40°C ambient operating range.
- Division I, Class I, II, and III.
- IECEx ia intrinsic safety
- EN60529 ingress protection level IP67.
- Ribbed casing for a secure grip
- Tested in accordance with the ANSI FL 1 standard using Energizer MAX® batteries
- Light modes : Beam

Logistics

- SAP
- E301393803
- MODEL NUMBER
- ISHH21
- EAN
- 7638900424485
- CU/SU
- 4
- CU DIMENSIONS (mm) (H,W,D)
- 222 x 55 x 55
- SU DIMENSIONS (mm) (H,W,D)
- 210 x 135 x 138
- SU DETAILS
- Unit box
- BATT/CU
- 0
- BATTERIES
- x2 Energizer Max Alkaline AA (Not Included)

Palletisation

	Battery	CU	SU	DU	XU	Pallet Layer	Pallet	mm	mm	Gross g	Net g
Battery											
CU	0							55	222	155	155
SU	0	4						135	138	715	620
DU	0	0	0					0	0	0	0
XU	0	0	0	0				0	0	0	0
Pallet Layer	0	160	40	0	0			675	1104	28600	24800
Without wood pallet	0	640	160	0	0	4		675	1104	114400	99200
With wood pallet	0	640	160	160	0	4		675	1104	114422	99200